## Printer Recalibration after Changing Paper

Last Modified on 10/02/2024 10:56 am EDT

- 1. Go to Start and find Devices and Printers in the Control Panel.
- 2. Right-click on the Cognitive Advantage 4 inch2 printer.



**Note:** If using the stylus that came with the truck computer, hold the button on the side of the stylus then choose the Printer icon. If using something other than the default stylus, hold on the Printer icon until a circle is drawn around the icon. Lift off the screen and the menu will display.

- 3. Go to Printing preferences / Cognitive Advantage 4 inch.
- 4. Select the Advanced Setup tab then choose More Settings.

Command Foote Custom Con		mands Import/Export settings About			About		
Options	Advanced	Setup	Dithen	ng	Stocks	Barco	de Fonts
Print Mode	-0	-	-				
0	Direct Them	nai	•	© Th	ermal Tra	nsfer	
Sensor Ty	ре						
C	Gap	0	Black Ba	r 🛛	N	one	
Present La	abel						
E	Disabled						
Distance Advance				0.00	i	nch	
Distance Reverse				0.00	i	nch	
Cutter/Per	eler Options -						
Enable Cutter				Enable Peeler Mode			
F	ull Cut After E	very Lab	el	*			
Settings -							
P	Disable Sett	ings Sen	t to the P	rinter			
P	rint Resolution			200	•	DPI	
Granhie O	otione			200			
araphic o	Direct Drint			00	ning Crow	hia	
Const Lab	Direct Frint	Vinter		0 30	oning Grap	Inic	
Export Lac	DAM	-nnter -			ACH		
0				O FL	Asn		_
D	elimiter:	Non	e 🔻		2	More Sett	ings

5. Select Calibrate. One inch of paper will come out of the printer.

Immediate C	ommands		-? <b>-</b> ×
Ethemet Set	up —		
IP :	0.0.0	DHCP : On	Off Off
Subnet :	0.0.0.0	LPD : On	○ Off
Gateway :	0.0.0.0	RTEL : On	Off Off
		Port :	
lane.		Send Ethemet D	ata to Printer
Actions —	4" Test	2" Test	Self-Test
			3 Calibrate

- 6. When done, select **Close** then **OK**.
- 7. Repeat Steps 2 6 and choose *Cognitive Advantage 4 inch2* for Step 3.